

AMENDMENT

Please enter the following amendments:

IN THE CLAIMS

Claims 1-9, 16-23 and 63-81, and 83-100 are pending. Claims 81, 83-87, and 95 are canceled without prejudice or disclaimer. Claim 98 is amended. The following is a claim listing showing the claim status.

1. (Previously Presented) A microcombustor comprising:

a first section comprising a combustion fuel channel having an inlet for connecting the microcombustor to a combustion fuel source and an outlet at a top surface of said first section; and

a second section disposed next to the first section;

the second section comprising:

a combustion chamber having an inlet in fluid communication with the outlet of the channel of the first section and an outlet capable of evacuating combustion exhaust products; and

an exhaust channel having an inlet in fluid communication with the outlet of the combustion chamber and an outlet at a surface of said second section;

wherein the combustion fuel channel and the exhaust channel are disposed on a same side with respect to the combustion chamber, so as to form a first heat exchanger;

wherein the first section and the second section are separated by a first plate;

and further comprising a second plate disposed on the side of the second section opposite the first section; wherein the second plate defines one side of the combustion chamber;

wherein the combustion chamber comprises a combustion catalyst and a space separates the combustion catalyst and the second plate;

wherein the space allows for fluid expansion and flow to the exhaust channel.

2. (original) The microcombustor of claim 1, wherein the combustion fuel channel and the exhaust channel are disposed in planes substantially parallel to each other.
3. (Previously Presented) The microcombustor of claim 2, wherein the combustion fuel channel and the exhaust channel are adjacent and substantially parallel to each other.
4. (original) The microcombustor of claim 1, wherein a first heat transfer layer is disposed between the first section and the second section.
5. (original) The microcombustor of claim 4, wherein a second heat transfer layer is disposed on the second section.
6. (previously presented) The microcombustor of claim 1, wherein the combustion chamber has a volume in the range of 0.02 and 0.002 ml.
7. (original) The microcombustor of claim 1, wherein a liquid evacuation system is disposed in the exhaust channel.
8. (original) The microcombustor of claim 7, wherein the liquid evacuation system comprises a wick.
9. (original) A fuel cell comprising the microcombustor of claim 1.
- 10-15. (canceled)
16. (original) A steam reformer, comprising
a microcombustor as defined in claim 1; and

a third section comprising a reformation channel having an inlet for supplying reformation fuel and an outlet for evacuating reformation products, wherein the exhaust channel and at least a portion of the reformation channel are disposed on a same side with respect to the combustion chamber, so as to form a second heat exchanger.

17. (original) The steam reformer of claim 16, wherein the exhaust channel and the reformation channel are disposed in planes substantially parallel to each other.

18. (previously presented) The steam reformer of claim 17, wherein the exhaust channel and the reformation channel are adjacent and substantially parallel to each other; and wherein the reformation channel comprises a reforming catalyst.

19. (original) The steam reformer of claim 16, wherein a second heat transfer layer is disposed between the second and third layers.

20. (original) The steam reformer of claim 16, wherein a reformation catalyst is disposed in the reformation channel.

21. (original) The steam reformer of claim 16, wherein a liquid evacuation system is disposed in the exhaust channel.

22. (original) The steam reformer of claim 21, wherein the liquid evacuation system comprises a wick.

23. (original) A fuel cell comprising the steam reformer of claim 16.

24-62. (canceled)

63. (Previously Presented) The microcombustor of claim 3 wherein the first section comprises a combustion fuel tube and an air tube.
64. (Previously Presented) The microcombustor of claim 3 wherein the combustion catalyst has a porosity of 30 to 95%.
65. (Previously Presented) The microcombustor of claim 3 wherein the combustion catalyst comprises a metal foam or a metal felt.
66. (Previously Presented) The microcombustor of claim 3 wherein the combustion catalyst has a thickness between 0.1 and 1 mm.
67. (Previously Presented) The microcombustor of claim 3, wherein a liquid evacuation system is disposed in the exhaust channel.
68. (Previously Presented) The microcombustor of claim 67, wherein the liquid evacuation system comprises a wick.
69. (Previously Presented) A fuel cell comprising the microcombustor of claim 68.
70. (Previously Presented) The microcombustor of claim 3, wherein the combustion catalyst has a pore volume of 5 to 98%
71. (Previously Presented) The microcombustor of claim 67, wherein the combustion catalyst has a pore volume of 30 to 95% and at least 50% of the of the catalyst's pore volume is composed of pores in the size range of 0.1 to 300 μm .

72. (Previously Presented) The microcombustor of claim 3, wherein at least 50% of the of the combustion catalyst's pore volume is composed of pores in the size range of 0.1 to 300 μm .

73. (Previously Presented) The microcombustor of claim 3, wherein at least 20% of the of the combustion catalyst's pore volume is composed of pores in the size range of 1 to 100 μm .

74. (Previously Presented) The microcombustor of claim 3, wherein the combustion chamber has a volume of 0.05 ml or less.

75. (Previously Presented) The microcombustor of claim 1, wherein the combustion chamber has a volume of 0.05 ml or less.

76. (Previously Presented) The microcombustor of claim 68, wherein the wick comprises fibers or foam.

77. (Previously Presented) The microcombustor of claim 71, wherein the combustion chamber has a volume of 0.05 ml or less.

78. (Previously Presented) The microcombustor of claim 73, wherein the combustion chamber has a volume of 0.05 ml or less.

79. (Previously Presented) The microcombustor of claim 3, wherein the combustion chamber has a volume in the range of 0.02 and 0.002 ml.

80. (Previously Presented) The microcombustor of claim 68, wherein the combustion chamber has a volume in the range of 0.02 and 0.002 ml.

81-87. (Canceled)

88. (Previously Presented) The microcombustor of claim 18 wherein the catalyst in the reformation channel is selected from the group consisting of CuZnAl, Pd/ZnO, and supported Ru, Pt, and Rh catalysts.

89. (Previously Presented) The microcombustor of claim 18 wherein the catalyst in the reformation channel comprises Pd/ZnO.

90. (Previously Presented) The microcombustor of claim 18 wherein the catalyst in the reformation channel comprises a metal foam.

91. (Previously Presented) The microcombustor of claim ~~85~~ 18 wherein the catalyst in the reformation channel has a porosity of at least 80%.

92. (Previously Presented) The microcombustor of claim 91 wherein the catalyst in the reformation channel comprises Pd.

93. (Previously Presented) The microcombustor of claim 18 wherein the catalyst in the reformation channel is disposed in a reforming chamber that is in thermal contact with the combustion chamber and wherein the reforming chamber has a volume of 0.05 ml or less.

94. (Previously Presented) The steam reformer of claim 18 wherein the catalyst in the reformation channel has a pore volume of 5 to 98% and at least 20% of the of the catalyst's pore volume is composed of pores in the size range of 0.1 to 300 μm .

95. (Canceled)

96. (Previously Presented) The steam reformer of claim 18 wherein the catalyst in the

reformation channel has a specific activity of greater than 1.5 mol methanol converted/(g catalyst)(hour) when tested at 400 °C, 25 millisecond contact time, and a reactant stream of 1:8 water:methanol ratio.

97. (Previously Presented) The steam reformer of claim 96 wherein the catalyst exhibits a pressure drop of less than 25 psig.

98. (Currently Amended) The steam reformer of claim ~~18~~ 85 wherein the catalyst in the reformation channel has a specific activity of greater than 2.5 mol methanol converted/(g catalyst)(hour) when tested at 400 °C, 25 millisecond contact time, and a reactant stream of 1:8 water:methanol ratio.

99. (Previously Presented) The steam reformer of claim 18 having an overall volume of less than 0.5 ml.

100. (Previously Presented) The steam reformer of claim 94 wherein the combustion catalyst has a pore volume of 5 to 98% and at least 20% of the of the catalyst's pore volume is composed of pores in the size range of 0.1 to 300 μm .

In The Drawings

A set of formal replacement drawings is submitted herewith.